

【新製品】 5軸制御本格的研削研磨マシニングセンタ

# OptiPro 「eSX150」



SPECIFICATIONS	eSX 150
<b>Work Spindle</b> Workpiece Diameter Range Spindle Speed Hydro-Expansion Chuck C-Axis Position and Hold	5 - 150 mm (.2" - 6") 1 - 500 rpm Standard Standard
<b>Tool Spindle</b> Maximum Tool Diameter Maximum Tool Weight Spindle Speed Power at Max Speed Tool Holder Style Twin Spindle	125 mm (5") 4 kg (8.8 lbs.) 1,000 - 22,000 rpm 12kW (15hp) HSK63F Optional
<b>Travels</b> X - Axis Travel Y - Axis Travel Z - Axis Travel B - Axis Travel C - Axis Travel	500 mm (20") 400 mm (16.2") 500 mm (20") -90° to 90° 0° to 360°
<b>Communication Interface</b> Ethernet USB	Standard Standard
<b>Automatic Tool Changer</b>	Optional
<b>Machine Dimensions</b> Width Depth Height Weight	2,040 mm (80") 1,960 mm (77") 1,960 mm (77") 3,630 kg (8,000 lbs.)
<b>Asphere Fabrication</b> <b>Freeform Fabrication</b>	Optional Optional

OptiWorks 株式会社

〒 541-0052 大阪市中央区安土町 1-2-4 ミツルプラザ 204 TEL/FAX 06-6264-7310  
HP/www.optiworks.jp E-Mail/sales@optiworks.jp

