

【新製品】 5軸制御本格的研削研磨マシニングセンタ

OptiPro 「PRO 80GTS」



SPECIFICATIONS*	PRO 80GTS
Work Spindle Work Diameter Range Spindle Speed Hydro-Expansion Chuck C-Axis Position and Hold	5 - 80 mm (.2" - 3.1") 50 - 1,500 rpm Standard Optional
Tool Spindle Maximum Tool Diameter Maximum Tool Weight Tool Spindle Speed Power at Max Speed Tool Holder Style Twin Spindle	75 mm (3") 2.5 kg (5.5 lbs.) 200 - 20,000 rpm 7kW (9.38hp) HSK63F Optional
Travels X - Axis Travel Y - Axis Travel Z - Axis Travel B - Axis Travel C - Axis Travel (optional)	250 mm (10") 12 mm (.5") 140 mm (5.5") -60° to 60° 0° to 360°
Communication Interface Ethernet USB	Standard Standard
Machine Dimensions Width Depth Height Weight	1,000 mm (39.4") 1,500 mm (59.1") 2,080 mm (81.9") 1,814 kg (4,000 lbs.)
Facility Requirements Electric Air Supply Coolant Water	460V +/- 5%, 30A (Alternative options upon request) 100 PSI, 4 scfm clean, dry air DI Water

OptiWorks 株式会社

〒 541-0052 大阪市中央区安土町 1-2-4 ミツルプラザ 204
HP/www.optiworks.jp E-Mail/sales@optiworks.jp

OptiWorks

TEL/FAX 06-6264-7310