

【新製品】 5軸制御本格的研削研磨マシニングセンタ

OptiPro 「PRO 80UFF」



SPECIFICATIONS*	PRO 80UFF
Work Spindle	
Work Diameter Range	10 - 80 mm (.2" - 3.1")
Spindle Speed	50 - 1,500 rpm
Hydro-Expansion Chuck	Standard
Vacuum Chuck	Standard
C-Axis Position and Hold	Optional
Travels	
X - Axis Travel	250 mm (10")
Y - Axis Travel	12 mm (.5")
Z - Axis Travel	140 mm (5.5")
B - Axis Travel	-60° to 60°
C - Axis Travel	0° to 360°
Communication Interface	
Ethernet	Standard
USB	Standard
Machine Dimensions	
Width	1,000 mm (39.4")
Depth	1,500 mm (59.1")
Height	2,080 mm (81.9")
Weight	1,814 kg (4,000 lbs.)
Facility Requirements	
Electrical	460V +/- 5%, 30A (Alternative options upon request)
Air Supply	100 PSI, 4 scfm clean, dry air
Coolant Water	DI water
Workpiece Probing	Standard
Tool Probing	Standard
Asphere Fabrication	Standard

OptiWorks 株式会社

〒 541-0052 大阪市中央区安土町 1-2-4 ミツルプラザ 204
HP/www.optiworks.jp E-Mail/sales@optiworks.jp

OptiWorks

TEL/FAX 06-6264-7310