

【新製品】 5軸制御本格的研削研磨マシニングセンタ

OptiPro 「SXL 500」



SPECIFICATIONS*	SXL 500
Work Spindle Work Diameter Range Spindle Speed Hydro-Expansion Chuck C-Axis Position and Hold	10 - 500 mm (.4" - 20") 1 - 200 rpm Standard Standard
Tool Spindle Maximum Tool Diameter Maximum Tool Weight Spindle Speed Power at Max Speed Tool Holder Style Coolant Through Spindle	300 mm (12") 6 kg (13.2 lbs.) 1,000 - 18,000 rpm 18kW (24hp) HSK63F Optional
Travels X - Axis Travel Y - Axis Travel Z - Axis Travel B - Axis Travel C - Axis Travel	1200 mm (48") 700 mm (28") 500 mm (20") -90° to 90° 0° to 360°
Communication Interface Ethernet USB	Standard Standard
Automatic Tool Changer	Optional
Machine Dimensions Width Depth Height Weight	2,820 mm (111") 2,920 mm (115") 2,900 mm (114") 5,750 kg (12,650 lbs.)
Workpiece Probing Tool Probing	Standard Standard

OptiWorks 株式会社

〒 541-0052 大阪市中央区安土町 1-2-4 ミツルプラザ 204
HP/www.optiworks.jp E-Mail/sales@optiworks.jp

OptiWorks

TEL/FAX 06-6264-7310